EASTERN RESINS

DECO SHIELD

DESCRIPTION:

DECO SHIELD is a 100% solids, USDA acceptable, clear epoxy flooring resin designed for color quartz floors and as a sealer for concrete. It will not blush or water spot and will bond to cold, damp surfaces. *DECO SHIELD* supports heavy industrial traffic, is resistant to fungus and mildew as well as being anti-microbial.

TYPICAL USES:

Color quartz flooring Binder for mortars Broadcast flooring Primer for mortar Sealing concrete

VISCOSITY: (@72°F)

Part A: 500 cps Part B: 200 cps Mixed: 275 cps

MIX RATIO BY VOLUME:

2 parts A to 1 part B

FEATURES

Good chemical resistance
Convenient 2 to 1 ratio by volume
Low viscosity
Tenacious bond to most substrates
USDA acceptable

CURE SCHEDULE:

Pot life @ 75°F: 18 minutes
Tack free: 4 hours
Full cure: 8 hours

PHYSICAL PROPERTIES:					
Compressive Strength	ASTM D695	12,000 psi			
Tensile Strength	ASTM D638	5,500 psi			
Elongation at Break	ASTM D638	5.00%			
Abrasion Resistance					
CS-17 Wheel, 1 kg load	ASTM D4060	0.10 gm loss			
Water Absorption (2 hour Boil)	ASTM D570	0.07%			
Flexural Strength	ASTM D790	7,800 psi			
Shore D Hardness	ASTM D2240	90			
Heat Distortion Temperature	ASTM D648	127°F			
Bond Strength to Concrete		100% concrete failure			

CHEMIC	AL RES	ISTA	NCE:
--------	--------	------	------

REAGENT

Water excellent
Low concentrations of acids excellent
Most Alkalis excellent
Oils/grease excellent